

## Implement Diagonal Reifen und Räder

Größe	PR	TT/TL	Load / Speed	Tragfähigkeit bei 40km/h	Profil	Pronar Felge	Anschluss
10.0/75-15.3	10	TL	123A8	1550 kg	F302	9.00x15.3	6/161/205 ET0 A2/VS 2650KG
10.0/75-15.3	14	TL	123A8	1900 kg	F302	9.00x15.3	6/161/205 ET0 A2/VS 2650KG
10.0/75-15.3	12	TL	126A8	1700 kg	KT-129A	9.00x15.3	6/161/205 ET0 A2/VS 2650KG
11.5/80-15.3	12	TL	135A8	2180 kg	KT-129	9.00x15.3	6/161/205 ET0 A2/VS 2650KG
11.5/80-15.3	12	TL	135A8	2180 kg	KT-129A	9.00x15.3	6/161/205 ET0 A2/VS 2650KG
11.5/80-15.3	14	TL	139A8	2430 kg	KT-129	9.00x15.3	6/161/205 ET0 A2/VS 2650KG
15.0/55-17 (380/55-17)	14	TL	141A8	2575 kg	F303	13.00x17	6/161/205 ET0 A2/VS
15.0/55-17 (380/55-17)	14	TL	141A8	2575 kg	F303	13.00x17	8/221/275 ET0 A2
19.0/45-17 (480/45-17)	14	TL	144A8	2800 kg	F304	16.00x17	6/161/205 ET0 A2/VS
19.0/45-17 (480/45-17)	14	TL	144A8	2800 kg	F304	16.00x17	6/161/205 ET-35 A2/VS
19.0/45-17 (480/45-17)	14	TL	144A8	2800 kg	F304	16.00x17	6/161/205 ET-70 A2/VS
19.0/45-17 (480/45-17)	14	TL	144A8	2800 kg	F304	16.00x17	8/221/275 ET0 A2/VS
500/50-17	14	TL	152A8	3550 kg	F304	16.00x17	6/161/205 ET0 A2/VS
500/50-17	14	TL	152A8	3550 kg	F304	16.00x17	6/161/205 ET-35 A2/VS
500/50-17	14	TL	152A8	3550 kg	F304	16.00x17	6/161/205 ET-70 A2/VS
500/50-17	14	TL	152A8	3550 kg	F304	16.00x17	8/221/275 ET0 A2/VS
10.5/80-18 (280/80-18)	14	TL	138A8	2360 kg	F302	9x18	6/161/205 ET0 A2
10.5/80-18 (280/80-18)	14	TL	138A8	2360 kg	F302	9x18	8/221/275 ET0 A2
12.5/80-18 (300/80-18)	12	TL	142A8	3000 kg	F302	11x18	6/161/205 ET0 A2
12.5/80-18 (300/80-18)	12	TL	142A8	3000 kg	F302	11x18	8/221/275 ET0 A2
13.0/65-18	16	TL	144A8	2575 kg	F302	11x18	6/161/205 ET0 A2
13.0/65-18	16	TL	144A8	2575 kg	F302	11x18	8/221/275 ET0 A2



F302



F303

Tianli



F304



KT-129 (AW)



KT-129 A (AS)

Cropmaster