



TGB 610

New Product Release Document

Marketing Department. Sept 23, 2020

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website www.ascensotyres.com



New Product Release Document

Release Month: September'20

Brand: ASCENSO

Tread Pattern : TGB 610

Tyre Construction: Bias

Type: Tubeless

Main Applications: Grader



List of Sizes

Size	PR		
13.00-24	12,16		
14.00-24	12,16		



Salient Features

Open Tread Design:

Optimum traction on soil, sand, rock or gravel

Reinforced Carcass:

Withstands grading operation

Abrasion Resistant Tread Compound: Ensures high service life and low operating cost





Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC		Inflation	Recommended load,kg (lbs)
		SW	OD	-		LI/SI or PR	Pressure	Speed/h(mph)
		mm	mm	mm	mm		Bar	40
		In	in	in	in		Psi	25
13.00-24	8				12 PR	3.0	2725	
		333		581 22.8	3823 150.5	143 A8	44	5995
		13.1				16 PR 149 A8	4.0	3250
							59	7150
14.00-24	8					12 PR 147 A8	2.8	3075
		362	1348	610	4032		40	6765
		14.2	53.0	24.0	158.7	16 PR 153 A8	3.8	3650
							55	8030

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover